

Proizvod / Product: HYDROSOL ELASTIK

IZJAVA O USKLAĐENOSTI
DECLARATION OF PERFORMANCE
Br. / No. 001/20-HDE

1. **Jedinstvena identifikacijska oznaka tipa proizvoda / Unique identification code of product**
08.02.02

2. **Predviđena primjena / Intended use**

Elastična malterna smjesa za vodonepropusnu zaštitu vanjskih i unutrašnjih horizontalnih i vertikalnih površina (CM P) / Elastic mortar compound for watertight protection of external and internal horizontal and vertical surfaces (CM P)

3. **Proizvođač / Manufacturer**

JUB d.o.o.
Dol pri Ljubljani 28
SI-1262 Dol pri Ljubljani
Slovenia
www.jub.eu

4. **Sistemi ocjenjivanja i provjere nepromjenjivosti osobina / System of AVCP**

Sistem 3 / System 3

5. **Tehnička specifikacija / Technical specification**

EN 14891:2017
BAS EN 14891:2018

6. **Certifikacijsko tijelo / Certification body**

ZAG Ljubljana, 1404, je izvršio određivanje tipa proizvoda u okviru sistema 3 /
ZAG Ljubljana, 1404, made Product type determination within the framework of
system 3



7. Deklarisana svojstva / Declared performance

Bitne karakteristike / Characteristic	Osobina / Declaration	Standard / Norm	Tehnička specifikacija / Technical specification
Otpornost na pozitivni pritisak vode / <i>Waterproofing</i>	Nema prodiranja vode / <i>No water penetration</i>	EN 14891, test method A.7	EN 14891:2017
Početa zatezna adhezijska čvrstoća / <i>Initial tensile adhesion strength</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.2	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja u vodi / <i>Tensile adhesion strength after water contact</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.3	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja na +70°C / <i>Tensile adhesion strength after heat ageing</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.5	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja u krečnoj otopini / <i>Tensile adhesion strength after contact with lime water</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.9	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja u hlorisanoj vodi / <i>Tensile adhesion strength after contact with chlorinated water</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.7	EN 14891:2017
Premoštavanje pukotina pri standardnim uslovima / <i>Crack bridging ability under standard conditions</i>	$\geq 0,75 \text{ mm}$	EN 14891, test method A.8.2	EN 14891:2017
Zatezna adhezijska čvrstoća nakon smrzavanja i odmrzavanja / <i>Liquid water permeability</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.6	EN 14891:2017

Karakteristike gore navedenog proizvoda su u skladu sa deklarisanim osobinama. Za izdavanje ove izjave o usklađenosti, u skladu sa Uredbom (EU) br. 305/2011, odgovoran je isključivo gore navedeni proizvođač /

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Potpisao za i u ime proizvođača / Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 01.07.2020

Danijel Lisičić,
Vođa razvoja / R&D manage



 ZAG 1404	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia 14 Unique identification code of product: 08.02.02 Declaration of performance No.: 001/20-HDE	
EN 14891:2017 BAS EN 14891:2018 Dispersion liquid-applied water impermeable product resistant to contact with chlorinated water (DM P)	
Waterproofing	No water penetration
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$



Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$
<i>Tensile adhesion strength after contact with lime water</i>	$\geq 0,5 \text{ N/mm}^2$
<i>Tensile adhesion strength after contact with chlorinated water</i>	$\geq 0,5 \text{ N/mm}^2$
<i>Tensile adhesion strength after freeze-thaw cycles</i>	$\geq 0,5 \text{ N/mm}^2$
<i>Crack bridging ability under standard conditions</i>	$\geq 0,75 \text{ N/mm}$

