

Proizvod / Product: HYDROSOL DECOR FLOOR INTERIOR

IZJAVA O USKLAĐENOSTI
DECLARATION OF PERFORMANCE
Br. / No. 001/21-HDF

1. **Jedinstvena identifikacijska oznaka tipa proizvoda / Unique identification code of product**
08.02.07

2. **Predviđena primjena / Intended use**

Pripremljena masa za hidroizolacijsku zaštitu i dekorativnu obradu unutrašnjih podnih površina (DM P) / Dispersion compound for waterproofing and decorative treatment of interior floors (DM P)

3. **Proizvođač / Manufacturer**

JUB d.o.o.

Dol pri Ljubljani 28

SI-1262 Dol pri Ljubljani

Slovenia

www.jub.eu

4. **Sistemi ocjenjivanja i provjere nepromjenjivosti osobina / System of AVCP Sistem 3 / System 3**

5. **Tehnička specifikacija / Technical specification**

EN 14891:2017

BAS EN 14891:2018

Prijavljena tijela / Notified Body:

ZAG 1404



6. Deklarisana svojstva / Declared performance

Bitne karakteristike / Characteristic	Osobina / Declaration	Standard / Norm	Tehnička specifikacija / Technical specification
Otpornost na pozitivni pritisak vode / <i>Waterproofing</i>	Nema prodiranja vode / <i>No water penetration</i>	EN 14891, test method A.7	EN 14891:2017
Početna zatezna adhezijska čvrstoća / <i>Initial tensile adhesion strength</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.2	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja u vodi / <i>Tensile adhesion strength after water contact</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.3	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja na +70°C / <i>Tensile adhesion strength after heat ageing</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.5	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja u krečnoj otopini / <i>Tensile adhesion strength after contact with lime water</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.9	EN 14891:2017
Zatezna adhezijska čvrstoća nakon čuvanja u hlorisanoj vodi / <i>Tensile adhesion strength after contact with chlorinated water</i>	$\geq 0,5 \text{ N/mm}^2$	EN 14891, test method A.6.7	EN 14891:2017
Premoštavanje pukotina pri standardnim uslovima / <i>Crack bridging ability under standard conditions</i>	$\geq 0,75 \text{ mm}$	EN 14891, test method A.8.2	EN 14891:2017
Zatezna adhezijska čvrstoća nakon smrzavanja i odmrzavanja / <i>Liquid water permeability</i>	NPD	EN 14891, test method A.6.6	EN 14891:2017

Karakteristike gore navedenog proizvoda su u skladu sa deklarisanim osobinama. Za izdavanje ove izjave o usklađenosti, u skladu sa Uredbom (EU) br. 305/2011, odgovoran je isključivo gore navedeni proizvođač /

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Potpisao za i u ime proizvođača: / Signed for and on behalf of the manufacturer by: Dol pri Ljubljani, 01.02.2021.

Danijel Lisičić,
Rukovodilac razvoja



 ZAG 1404	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia 21 Unique identification code of product: 08.02.07 Declaration of performance No.: 001/21-HDF	
EN 14891:2017 Dispersion liquid-applied water impermeable product resistant to contact with chlorinated water (DM P)	
Waterproofing	No water penetration
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$
Tensile adhesion strength after contact with chlorinated water	$\geq 0,5 \text{ N/mm}^2$
Crack bridging ability under standard conditions	$\geq 0,75 \text{ mm}$

