

Proizvod / Product: JUBIZOL AEROGEL FINISH S 1.5 / 2.0

IZJAVA O USKLAĐENOSTI
DECLARATION OF PERFORMANCE
Br. / No. 001/20-AGG

1. **Jedinstvena identifikacijska oznaka tipa proizvoda / Unique identification code of product**
10.02.50

2. **Namjena proizvoda / Intended use**

Vanjski malter na bazi organskih veziva za dekorativnu zaštitu fasadnih zidnih površina / External render based on organic binder for decorative protection of facade walls

3. **Proizvođač / Manufacturer**

JUB d.o.o.

Dol pri Ljubljani 28

SI-1262 Dol pri Ljubljani

Slovenia

www.jub.eu

4. **Sistem ocjene uskladenosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnička specifikacija / Technical specification**

EN 15824



6. Deklarisana svojstva / Declared performance

Karakteristike / Characteristic	Deklaracija / Declaration	Standard / Norm	Tehnička specifikacija / Technical specification
Odgovor na vatru / Reaction to fire	F	EN 13501-1	EN 15824:2017
Čvrstoća prijanjanja / Bond strength	> 0,3 MPa	EN 1542	EN 15824:2017
Toplinska prevodljivost $\lambda_{10, \text{suh}}$ / Thermal conductivity $\lambda_{10, \text{dry}}$	0,83 W/mK, P=50%	EN 1745	EN 15824:2017
Paropropusnost / Water vapour permeability	V1 (visoka) / V1 (high)	EN ISO 7783-2	EN 15824:2017
Upijanje vode / Water absorption	W3 (nisko) / W3 (low)	EN 1062-3	EN 15824:2017
Oslobađanje opasnih tvari / Release of dangerous substances	Pogledaj sigurnosni list / See Safety data sheet		EN 15824:2017

7. Proizvod je također komponenta vanjskog toplinsko-izolacionog sistema sa žbukom / malterom / Product is also component of external thermal insulation composite system with render

JUBIZOL EPS, ETA-09/0393
JUBIZOL MW, ETA-10/0334

ZAG Ljubljana 1404-CPR-2792
ZAG Ljubljana 1404-CPR-2793

Karakteristike proizvoda, navedene iznad, su u skladu sa deklarisanim svojstvima. Za izdavanje izjave o usklađenosti, u skladu sa Uredbom (EU) br. 305/2011, odgovoran je isključivo gore naveden proizvođač /

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above

Potpisao za i u ime proizvođača / Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 16.10.2020

Danijel Lisičić,
Vodja razvojnega področja



 1404 20	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia Unique identification code of product: 10.02.50 Declaration of performance No.: 001/20-AGG	
EN 15824:2017	
<i>External render based on organic binder for decorative protection of facade walls</i>	
Reaction to fire	F
Bond strength	> 0,3 MPa
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability	V1
Water absorption	W3
Release of dangerous substances	See Safety data sheet
www.jub.eu	

