

Proizvod / Product: JUBIZOL MICROAIR FIX

IZJAVA O USKLAĐENOSTI
DECLARATION OF PERFORMANCE
Br. / No. 001/19-JMI

1. **Jedinstvena identifikaciona oznaka tipa proizvoda / Unique identification code of product**
11.01.12

2. **Namjena proizvoda / Intended use**

Malter smjesa (ljepilo) za vanjsku i unutrašnju upotrebu (GP) / Factory-made rendering mortar for internal and external use (GP)

3. **Proizvođač / Manufacturer**

JUB d.o.o.
Dol pri Ljubljani 28
SI-1262 Dol pri Ljubljani
Slovenia
www.jub.eu

4. **Sistemi ocjene usklađenosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnička specifikacija / Technical specification**

EN 998-1:2016
BAS EN 998-1: 2018



6. Deklarisana svojstva / Declared performance

Bitne karakteristike / Characteristic	Osobina / Declaration	Standard / Norm	Tehnička specifikacija / Technical specification
Odgovor na vatru / Reaction to fire	F	EN 13501-1	EN 998-1:2016 BAS EN 998-1:2018
Pritisna tvrdoća / Compressive strength	CS IV	EN 1015-11	EN 998-1:2016 BAS EN 998-1:2018
Prionljivost / Adhesion	> 0,5 MPa – FP: B	EN 1015-12	EN 998-1:2016 BAS EN 998-1:2018
Toplotna prevodljivost $\lambda_{10, \text{su}} /$ Thermal conductivity $\lambda_{10, \text{dry}}$	0,83 W/mK, P=50%	EN 1745	EN 998-1:2016 BAS EN 998-1:2018
Paropropusnost (μ) / Water vapour Permeability (μ)	< 15	EN 1015-19	EN 998-1:2016 BAS EN 998-1:2018
Upijanje vode / Water absorption	W2	EN 1015-18	EN 998-1:2016 BAS EN 998-1:2018
Trajnost / Durability	NPD		EN 998-1:2016 BAS EN 998-1:2018
Opasne supstance / Dangerous substances	NPD		EN 998-1:2016 BAS EN 998-1:2018

7. Proizvod je također komponenta vanjskog termoizolacionog sistema sa malterom /
Product is also component of external thermal insulation composite system with render

JUBIZOL EPS, ETA-09/0393
JUBIZOL PB EPS, ETA-13/0633
JUBIZOL S70, ETA-08/0236

ZAG Ljubljana 1404-CPR-2792
ZAG Ljubljana 1404-CPR-3215
ZAG Ljubljana 1404-CPR-3222

Karakteristike gore navedenog proizvoda su u skladu sa navedenim osobinama. Za izdavanje ove izjave o usklađenosti, u skladu sa Uredbom (EU) br. 305/2011, odgovoran je isključivo gore navedeni proizvođač /

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.



Potpisao za i u ime proizvođača / Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 05.11.2019

Danijel Lisičić,
Rukovodilac razvoja



CE	
13	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia	
Unique identification code of product: 11.01.12 Declaration of performance No.: 001/19-JMI	
EN 998-1:2016	
<i>Factory-made rendering mortar for internal and external use (GP)</i>	
Reaction to fire	F
Compressive strength	CS IV
Adhesion	> 0,5 MPa – FP: B
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability (μ)	< 15
Water absorption	W2
www.jub.eu	

