

Izdelek / Product: **JUBIZOL UNIWOOL FIX**

**IZJAVA O LASTNOSTIH**  
**DECLARATION OF PERFORMANCE**  
**Št. / No. 001/19-JUW**

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**  
11.01.23

2. **Predvidena uporaba / Intended use**

**Maltna zmes za zunaj in znotraj (GP) / Factory-made rendering mortar for internal and external use (GP)**

3. **Proizvajalec / Manufacturer**

JUB d.o.o.  
Dol pri Ljubljani 28  
SI-1262 Dol pri Ljubljani  
Slovenia  
[www.jub.eu](http://www.jub.eu)

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnična specifikacija / Technical specification**

EN 998-1:2016

6. **Navedene lastnosti / Declared performance**

<b>Bistvene značilnosti / Characteristic</b>	<b>Lastnost / Declaration</b>	<b>Standard / Norm</b>	<b>Tehnična specifikacija / Technical specification</b>
<b>Odziv na ogenj / Reaction to fire</b>	<b>F</b>	EN 13501-1	EN 998-1:2016
<b>Tlačna trdnost / Compressive strength</b>	<b>CS IV</b>	EN 1015-11	EN 998-1:2016
<b>Sprijemna trdnost / Adhesion</b>	<b>&gt; 0,5 MPa – FP: B</b>	EN 1015-12	EN 998-1:2016
<b>Toplotna prevodnost <math>\lambda_{10,suh}</math> / Thermal conductivity <math>\lambda_{10,dry}</math></b>	<b>0,83 W/mK, P=50%</b>	EN 1745	EN 998-1:2016



<b>Paroprepusnost (<math>\mu</math>) / Water vapour Permeability (<math>\mu</math>)</b>	<b>&lt; 20</b>	EN 1015-19	EN 998-1:2016
<b>Vpijanje vode / Water absorption</b>	<b>W2</b>	EN 1015-18	EN 998-1:2016
<b>Trajnost / Durability</b>	<b>NPD</b>		EN 998-1:2016
<b>Nevarne snovi / Dangerous substances</b>	<b>NPD</b>		EN 998-1:2016

7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom / Product is also component of external thermal insulation composite system with render**

**JUBIZOL EPS, ETA-09/0393  
JUBIZOL MW, ETA-10/0334**

**ZAG Ljubljana 1404-CPR-2792  
ZAG Ljubljana 1404-CPR-2793**

**Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.**

*The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

**Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:**

Dol pri Ljubljani, 05.11.2019

Danijel Lisičić,  
Vodja razvojnega področja





13

JUB d.o.o.  
Dol pri Ljubljani 28  
SI – 1262 Dol pri Ljubljani  
Slovenia

Unique identification code of product: 11.01.23  
Declaration of performance No.: 001/19-JUW

**EN 998-1:2016**

*Factory-made rendering mortar for internal and external use  
(GP)*

Reaction to fire	F
Compressive strength	CS IV
Adhesion	> 0,5 MPa – FP: B
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability ( $\mu$ )	< 20
Water absorption	W2

www.jub.eu

