

Izdelek / Product: **JUBIZOL LEPILNA MALTA WINTER**



**IZJAVA O LASTNOSTIH**  
**DECLARATION OF PERFORMANCE**  
Št. / No. **001/21-JLMW**

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**  
11.01.31

2. **Predvidena uporaba / Intended use**

**Maltna zmes za zunaj in znotraj (GP) / Factory-made rendering mortar for internal and external use (GP)**

3. **Proizvajalec / Manufacturer**

JUB d.o.o.

Dol pri Ljubljani 28

SI-1262 Dol pri Ljubljani

Slovenia

[www.jub.eu](http://www.jub.eu)

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnična specifikacija / Technical specification**

EN 998-1

6. **Navedene lastnosti / Declared performance**

Bistvene značilnosti / Characteristic	Lastnost / Declaration	Standard / Norm	Tehnična specifikacija / Technical specification
<b>Odziv na ogenj / Reaction to fire</b>	<b>F</b>	EN 13501-1	EN 998-1:2016
<b>Tlačna trdnost / Compressive strength</b>	<b>CS IV</b>	EN 1015-11	EN 998-1:2016
<b>Sprijemna trdnost / Adhesion</b>	<b>&gt; 0,5 MPa – FP: B</b>	EN 1015-12	EN 998-1:2016
<b>Toplotna prevodnost <math>\lambda_{10, suh}</math> /</b>	<b>0,83 W/mK,</b>	EN 1745	EN 998-1:2016



<i>Thermal conductivity <math>\lambda_{10,dry}</math></i>	<b>P=50%</b>		
<b>Paroprepusnost / Water vapour permeability</b>	<b>&lt; 20</b>	EN 1015-19	EN 998-1:2016
<b>Vpijanje vode / Water absorption</b>	<b>W2</b>	EN 1015-18	EN 998-1:2016
<b>Trajnost / Durability</b>	<b>NPD</b>		EN 998-1:2016
<b>Nevarne snovi / Dangerous substances</b>	<b>NPD</b>		EN 998-1:2016

7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom / Product is also component of external thermal insulation composite system with render**

JUBIZOL EPS, ETA-09/0393  
 JUBIZOL MW, ETA-10/0334  
 JUBIZOL PB EPS, ETA-13/0633  
 JUBIZOL PB MW, ETA-13/0632  
 JUBIZOL S70, ETA-08/0236  
 JUBIZOL XPS, ETA-07/0028

ZAG Ljubljana 1404-CPR-2792  
 ZAG Ljubljana 1404-CPR-2793  
 ZAG Ljubljana 1404-CPR-3215  
 ZAG Ljubljana 1404-CPR-3216  
 ZAG Ljubljana 1404-CPR-3222  
 ZAG Ljubljana 1404-CPR-2794

Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.

*The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

**Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:**

Dol pri Ljubljani, 21.09.2021

Danijel Lisičić,  
 Vodja razvojnega področja




JUB d.o.o.  
 Dol pri Ljubljani 28  
 SI-1262 Dol pri Ljubljani  
 Slovenija



<b>CE</b>	
15	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia	
Unique identification code of product: 11.01.31 Declaration of performance No.: 001/21-JLMW	
<b>EN 998-1:2016</b>	
<i>Factory-made rendering mortar for internal and external use (GP)</i>	
Reaction to fire	F
Compressive strength	CS IV
Adhesion	> 0,5 MPa – FP: B
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability ( $\mu$ )	< 20
Water absorption	W2
<a href="http://www.jub.eu">www.jub.eu</a>	

