JUB kemična industrija d.o.o.
Dol pri Ljubljani 28, SI-1262 Dol pri Ljubljani, Slovenia
T: +386 1 588 41 83, F: +386 1 588 42 50, E: jub@jub.si
www.jub.eu
Member of JUB group

Produkt / *Product*: **JUBIZOL SKLOTEXTILNÁ MRIEŽKA 160g**

VYHLÁSENIE O PARAMETROCH
DECLARATION OF PERFORMANCE
Č. / *No.* **001/21-M160G**

1. **Jedinečný identifikačný kód typu výrobku:**/ *Unique identification code of product*
   15.04.21

2. **Zamýšľané použitie** / *Intended use*

   Spevňujúca sklotextilná mriežka 160 g pre vonkajšie tepelnoizolačné fasádne systémy / *Alkaline resistant reinforcement mesh 160 g for external thermal insulation composite system (ETICS)*

3. **Výrobca** / *Manufacturer*

   JUB d.o.o.
   Dol pri Ljubljani 28
   SI-1262 Dol pri Ljubljani
   Slovenia
   www.jub.eu

4. **Systém posudzovania a overovania nemennosti parametrov výrobku** / *System of AVCP*

   Systém 2+ / *System 2+*

5. **Technická špecifikácia** / *Technical specification*

   EAD 040083-00-0404

6. **Deklarované parametre** / *Declared performance*

Základné vlastnosti / *Characteristic*	**Parametre** / *Declaration*	**Norma** / *Norm*	**Technické špecifikácie**/ *Technical specification*
Pevnosť v ťahu v čase - stredná hodnota (pozdĺžna a priečna) / *Residual strength after ageing - mean value (warp and weft)*	**≥ 20 N/mm**		EAD 040083-00-0404

Relatívna pevnosť v ťahu v čase v porovnaní s pevnosťou neopotrebovanej siete (pozdĺžna a priečna) / *Relative residual resistance after ageing of the strength in the as delivered state (warp and weft)*	**≥ 50 %**		EAD 040083-00-0404

7. **Výrobok je zároveň súčasťou vonkajšieho tepelnoizolačného systému s omietkou** / *Product is also component of external thermal insulation composite system with render*

JUBIZOL EPS, ETA-09/0393	**ZAG Ljubljana 1404-CPR-2792**
JUBIZOL MW, ETA-10/0334	**ZAG Ljubljana 1404-CPR-2793**
JUBIZOL PB EPS, ETA-13/0633	**ZAG Ljubljana 1404-CPR-3215**
JUBIZOL PB MW, ETA-13/0632	**ZAG Ljubljana 1404-CPR-3216**
JUBIZOL S70, ETA-08/0236	**ZAG Ljubljana 1404-CPR-3222**
JUBIZOL XPS, ETA-07/0028	**ZAG Ljubljana 1404-CPR-2797**

Vyššie uvedené vlastnosti produktu sú v súlade s uvedenými vlastnosťami. Na účely vydania tohto vyhlásenia o parametroch v súlade s nariadením (EÚ) č. 305/2011 je výhradne zodpovedný výrobca uvedený vyššie.
The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, *under the sole responsibility of the manufacturer identified above.*

Podpísané za a v mene výrobcu / Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 07.07.2021

Danijel Lisičić,
Vedúci vývoja / *R&D manager*

JUB d.o.o.
Dol pri Ljubljani 28
SI-1262 Dol pri Ljubljani
Slovenija

CE	
1404	
JUB d.o.o. Dol pri Ljubljani 28 SI – 1262 Dol pri Ljubljani Slovenia Unique identification code of product: 15.04.21 Declaration of performance No.: 001/21-M160G	
EAD 040083-00-0404	
Alkaline resistant reinforcement mesh 160 g for external thermal insulation composite system	
Residual strength after ageing - mean value (warp and weft)	≥ 20 N/mm
Relative residual resistance after ageing of the strength in the as delivered state (warp and weft)	≥ 50 %
www.jub.eu	