

TECHNICAL SHEET 21.03.19-EN



EPS 120

White plain EPS 120

1. Product description

Thermal insulation boards made of expanded polystyrene.

2. Technical data

Board dimension: 1000 x 500 mm
Thickness: 10 mm to 300 mm

3. Resistance

Temperature resistance: 70°C on a long-term basis.

4. Standard

EN 13163:2012+A1:2015

5. Quality

The quality characteristics of the product are determined by European standards. Achieving the declared or prescribed level of quality is ensured by the ISO 9001 quality control system, which includes daily product quality checks in our own laboratories. In manufacturing process, we strictly comply with European standards in the field of energy saving, environmental protection and ensuring safety and health at work, which is confirmed by ISO 50001, ISO 14001 and ISO 45001 certificates.

6. Field of use

- for thermal insulation of flat and slanted roofs;
- for thermal insulation of floors with normal load;

7. Application

Depending on the purpose of use, thermal insulation boards are installed by gluing, mechanical fastening or they

are laid freely.

8. Packaging

Thermal insulation boards are in a package of 0.25 m³, wrapped in an opaque PE-foil. Each package contains a declaration sheet in accordance with the SIST EN 13172 standard.

9. Storage

Store in covered areas, away from sources of heat and flame, do not expose to UV rays, avoid contact with incompatible materials/chemicals.

10. Waste management

The manufacturer guarantees that all its packaging is included in the waste packaging management system (Ur.I.RS, No. 84/06 with all amendments and additions).

11. Technical specifications - 1

CE- technical code EPS-EN 13163-L3-W3-T2-S5-P10-DS(N)5-BS170-CS(10)120

Essential characteristic	Mark	Performance	Unit	Declared	Standard
Length	L	1000	mm	L3	EN 822
Width	W	500	mm	W3	EN 822
Thickness	T	20-300	mm	T2	EN 823
Squerness	S	1000/500	mm	S5	EN 824
Flatness	P	1000/500	mm	P10	EN 825
Dimensional stability	DS	1000/500	%	DS(N)5	EN 1603
Compressive stress at 10% def.	CS	-	kPa	CS(10)120	EN 826
Bending strength	BS	-	kPa	BS170	EN 12089
Tensile strength	-	-	-	-	-
Water vapour diffusion resistance	μ	20-50	-	-	EN 12086
Thermal conductivity	λD	0,036	W/mK	0,036	EN 12667
Fire resistance (Euroclass)	-	E	-	E	EN 13501-1

12. Technical specifications - 2

Essential characteristic	Mark	Performance											
Thickness (mm)	d	10	20	30	40	50	60	70	80	90	100	110	120
Thermal resistance (m ² K/W)	RD	0,25	0,55	0,80	1,10	1,35	1,65	1,90	2,20	2,50	2,75	3,05	3,30
Thermal transmittance (W/m ² K)	U	3,4	1,80	1,20	0,90	0,72	0,60	0,51	0,45	0,40	0,36	0,33	0,30
Thickness (mm)	d	130	140	150	160	180	200	220	240	250	260	280	300
Thermal resistance (m ² K/W)	RD	3,60	3,85	4,15	4,40	5,00	5,55	6,10	6,65	6,90	7,20	7,75	8,30
Thermal transmittance (W/m ² K)	U	0,28	0,26	0,24	0,23	0,20	0,18	0,16	0,15	0,14	0,14	0,13	0,12

13. Certificate

Declaration of properties, in accordance with the European construction products regulation CPR and with the European standard EN 13163:2012+A1:2015.

Denomination and date of publishing: , 14.05.2025