

TECHNICAL SHEET 05.02.02-EN



HYDROSOL Self adhesive sealing strip

Sealing strip

1. Description, Application

HYDROSOL Self adhesive sealing strip 100 is a permanently elastic butyl tape coated with fleece, which has high adhesive strength and tear resistance. It is designed for reinforcing waterproofing compounds on horizontal and vertical (external and internal) corner surfaces. It allows excellent combination with polymer dispersions, flexible mineral sealing slurries, and reactive resins.

2. Technical data

Packaging (1 piece)	10 m
Tape thickness	0.8 mm
Tape width	100 mm
Temperature stability	-20°C do +90°C

3. Surface Preparation

The preparation of the substrate depends on the appropriately used waterproofing system.

4. Installation instructions

HYDROSOL Self adhesive sealing strip should be cut to the desired length. Remove half of the silicone tape and then evenly apply the sealing tape to the surface. Ensure that the fold line extends into the extreme corner or angle. After applying the tape to the surface, smooth it out further by hand or with a trowel to achieve maximum adhesion. Repeat the process with the other half. It's crucial that the sealing tape is correctly positioned on the first attempt because corrections are possible only under specific conditions and depend on the substrate. In case of tape damage, it should be replaced with a new one for safety reasons. Ensure a cm overlap at the junction between two tapes or at a corner element.

5. Storage, Transportation Conditions and Durability

The product can be stored in its originally sealed packaging for up to 24 months in a cool, dry place.

6. Other Information

Technical instructions contained in this brochure are provided on the basis of JUB's experience and are given as a guideline to achieve the optimum results. All assurances for product characteristics (including shade) apply only to the complete JUB system. JUB cannot accept any responsibility for damage caused by incorrect selection of a product, incorrect use or unprofessional work.

Safety measures: Follow the instructions on the safety data sheet of the product.

This technical sheet supplements and replaces all preceding editions. JUB reserves the right to change and supplement data in the future.

Designation and date of issue: TDS 097/25-čad, 11.11.2025