

TECHNICAL SHEET 05.06.14-EN



JUBIZOL Clip-on bead

Clip-on drip bead for ALU base bead

1. Description, usability

JUBIZOL SNAP-ON PROFILE is used to extend the drip edge on aluminum base strips. It reduces the risk of cracks forming on the external joints of aluminum strips and on the connections of these strips with the insulation layer. The profile is fitted onto the outer edge of JUBIZOL Aluminum base strips.

Features:

- Directed rainwater drainage
- Precise shaping of the edge
- Prevents the formation of cracks
- Clean finish
- Easy to use

2. Packaging

25 pieces / box;
62.5 m / box;
40 boxes / pallet;
2500 m / pallet

3. Technical data

Product name	JUBIZOL SNAP-ON PROFILE
Material	Polyvinyl chloride (PVC)
Batten length	2500 mm
Mesh attachment method	Welding

4. Installation

JUBIZOL SNAP-ON PROFILE is placed on the outer edge of the JUBIZOL Alu drip ledge immediately after gluing

the thermal insulation layer. The reinforcement mesh, which is attached to JUBIZOL SNAP-ON PROFILE is removed from the thermal insulation coating with a spatula. Then, the mesh of the profile is pressed into a thin layer of adhesive mortar, applied with a notched stainless steel trowel in a suitably wide band on the thermal insulation layer (above the aluminum base strip). It is aligned using a water scale. Longitudinal joints of the stacking profiles must overlap with their own mesh by at least 10 cm. The adhesive mortar, squeezed through the reinforcing mesh of the stacking profile on the frontal surface of the thermal insulation layer, is spread out as much as possible, and any excess mortar is removed. The main reinforcement mesh is dropped vertically over the entire stacking profile, and at its bottom edge, it is cut with a wallpaper knife at a 45° angle. The entire JUBIZOL stacking profile is covered with adhesive mortar.

5. Instructions for safe use of the product

Safety handling instructions, first aid measures, fire protection measures, measures in case of accidental releases, special storage instructions, required personal protective equipment, waste handling instructions, special transport requirements, and other legally prescribed information are provided in the product's safety data sheet. In addition to these instructions, it is necessary to follow the guidelines and regulations for safety in construction, facade work, and painting when installing the product.

6. Storage, transportation conditions and durability

Packed in cardboard boxes. Store in a dry and covered area at a temperature of +5°C to +40°C. Transport in a horizontal position. Shelf life when stored in the original sealed and undamaged packaging: at least months.

7. Other information

The technical instructions in this brochure are provided on the basis of JUB's experience and are given as a guideline for achieving the optimum results. JUB cannot accept any responsibility for the damage caused by incorrect selection of a product, incorrect use or unprofessional work.

Safety measures: Follow the instructions on the safety data sheet of the product.

This technical sheet supplements and replaces all preceding editions. JUB reserves the right to change and supplement data in the future.

Designation and date of issue: TDS 127/25-pek, 15.12.2025