

TECHNICAL SHEET 04.01.29-EN



DECOR Wax

Glossy gel wax

1. Description, Application

DECOR Wax is a water-based wax dispersion product designed to protect wall surfaces treated with DECOR Marmorin - a decorative acrylic putty.

Coating surfaces with DECOR Wax enhances their gloss and water repellency, making them easier to clean and maintain.

2. Technical data

Packaging	300 g	
Density	~0.96 kg/dm ³	
Content of vaporous substance (VOC)	21.49 g/l	
The EU VOC requirement - category	A/g<30	
Water dilution mass	0 %	
Water dilution volume		
Drying time	Touch dry	~2 h
T = +20 °C, relative air humidity = 65 %	Suitable for polishing	~24 h
Consumption	~20 g/m ² (for a two-coat application)	
Recommended number of layers	2	

3. Installation Conditions

The temperature of air and wall surface should not be lower than +5 °C and not higher than +35 °C, and relative air

humidity should not exceed 80 %.

4. Preparation

Just mix the content of the pot well before use.

5. Instructions for use

Apply DECOR Wax to the final, already smoothed or polished layer of decorative filler DECOR Marmorin using a decorative trowel in one or two layers. The second layer can be applied once the first layer is completely dry, i.e., after 2 hours, or when the surface is no longer sticky to the touch. Once the surface treated with DECOR Wax is completely dry, you can start polishing. Polishing can be done manually or with a machine. For machine polishing, use tool made of sheep wool. Start polishing at a slow speed; as the surface begins to shine, you can increase the speed slightly, being careful not to overheat the surface, as this could damage the final appearance of the decorative technique. For manual polishing, use a designated decorative trowel to cover the entire surface with even strokes and a bit more pressure.

Thoroughly clean the tools with water immediately after use.

6. Storage, Transportation Conditions and Durability

Storage and transportation at temperature +5°C to + 25°C, protected from the direct sunlight, out of reach of children, **MUST NOT FREEZE!!**

Durability when stored in originally sealed and undamaged packaging: at least 24 months.

7. Other Information

Technical instructions are given based on our experiences and are given as a guideline for achieving optimal results. We cannot take any responsibility for the damage, caused by incorrect selection of a product, incorrect use or unprofessional work. JUB also bears no responsibility in cases where the substrate for the application of our products is prepared inadequately or with materials of inadequate quality from other manufacturers. In the case of applying our products to existing substrates of old coatings or pre-prepared substrates with materials from other manufacturers, it is obligatory to make appropriate test fields with all the intended applications of JUB products, in accordance with the technical instructions, before starting the work.

Safety measures: Follow the instructions on the safety data sheet of the product.

This technical sheet supplements and replaces all preceding editions. JUB reserves the right to change and supplement data in the future.

Denomination and date of publishing: TRC-118/26-čad, 17.04.2026