

Izdelek / Product: **JUBIZOL LEPILNA MALTA GROBA**



IZJAVA O LASTNOSTIH
DECLARATION OF PERFORMANCE
Št. / No. 001/18-JLMG

1. **Enotna identifikacijska oznaka tipa proizvoda / Unique identification code of product**
11.01.24

2. **Predvidena uporaba / Intended use**

Maltna zmes za zunaj in znotraj (GP) / Factory-made rendering mortar for internal and external use (GP)

3. **Proizvajalec / Manufacturer**

JUB d.o.o.

Dol pri Ljubljani 28

SI-1262 Dol pri Ljubljani

Slovenia

www.jub.eu

4. **Sistemi ocenjevanja in preverjanja nespremenljivosti lastnosti / System of AVCP**

Sistem 4 / System 4

5. **Tehnična specifikacija / Technical specification**

EN 998-1

6. **Navedene lastnosti / Declared performance**

Bistvene značilnosti / Characteristic	Lastnost / Declaration	Standard / Norm	Tehnična specifikacija / Technical specification
Odziv na ogenj / Reaction to fire	NPD	EN 13501-1	EN 998-1:2016
Tlačna trdnost / Compressive strength	CS IV	EN 1015-11	EN 998-1:2016
Sprijemna trdnost / Adhesion	> 0,5 MPa – FP: B	EN 1015-12	EN 998-1:2016



Toplotna prevodnost $\lambda_{10, \text{suh}}$ / <i>Thermal conductivity</i> $\lambda_{10, \text{dry}}$	0,83 W/mK, P=50%	EN 1745	EN 998-1:2016
Paroprepusnost / <i>Water vapour permeability</i>	< 20	EN 1015-19	EN 998-1:2016
Vpijanje vode / <i>Water absorption</i>	W2	EN 1015-18	EN 998-1:2016
Trajnost / <i>Durability</i>	NPD		EN 998-1:2016
Nevarne snovi / <i>Dangerous substances</i>	NPD		EN 998-1:2016

7. **Proizvod je tudi komponenta zunanjega toplotnoizolacijskega sistema z ometom /**
Product is also component of external thermal insulation composite system with render

JUBIZOL EPS, ETA-09/0393
 JUBIZOL MW, ETA-10/0334
 JUBIZOL PB EPS, ETA-13/0633
 JUBIZOL PB MW, ETA-13/0632
 JUBIZOL S70, ETA-08/0236
 JUBIZOL XPS, ETA-07/0028

ZAG Ljubljana 1404-CPR-2792
 ZAG Ljubljana 1404-CPR-2793
 ZAG Ljubljana 1404-CPD-1985
 ZAG Ljubljana 1404-CPD-1984
 ZAG Ljubljana 1404-CPD-1332
 ZAG Ljubljana 1404-CPR-2794

Lastnosti proizvoda, navedenega zgoraj, so v skladu z navedenimi lastnostmi. Za izdajo te izjave o lastnostih je v skladu z Uredbo (EU) št. 305/2011 odgovoren izključno proizvajalec, naveden zgoraj.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Podpisal za in v imenu proizvajalca / Signed for and on behalf of the manufacturer by:

Dol pri Ljubljani, 13.02.2018

Danijel Lisičić,
 Vodja razvojnega področja






JUB d.o.o.
 Dol pri Ljubljani 28
 SI – 1262 Dol pri Ljubljani
 Slovenia
 18

Unique identification code of product: 11.01.24
 Declaration of performance No.: 001/18-JLMG

EN 998-1:2016

*Factory-made rendering mortar for internal and external use
 (GP)*

Compressive strength	CS IV
Adhesion	> 0,5 MPa – FP: B
Thermal conductivity $\lambda_{10,dry}$	0,83 W/mK, P = 50% (value from EN 1745)
Water vapour permeability	< 20
Water absorption	W2